

SMART

VOICE MESSENGER MODEL VM-1

SMART VOICE MESSENGER is a stand alone message playback unit specially designed for outdoor use.

The message is stored electronically in hindi and English.

Unit comes with external volume control.

The construction is Aluminum with fully dust and rain proof housing.

Two Stainless Steel switch are provided for activation .



CONNECTIONS: -

- 1) Connect the power supply 220 VAC/ 110 VAC

TECHNICAL SPECIFICATIONS: -

ELECTRICAL PERFORMANCE: -

Audible range frequency response 300 - 3400 Hz.
output max 3 Watts

ELECTRICAL REQUIREMENTS: -

Connection method PCB terminal block type.
Fuse 2 Amp 2AG fast blows.
Power supply 220 VAC / 110 VAC.

ENVIRONMENTAL: -

Temperature 0 to +60 C.
Humidity 0 to 95% Rh non-condensing.
Enclosure Dustproof fully gasketed.

MECHANICAL: -

Body ALUMINUM.
Dimension of ABS BOX 280 x 250 x 100 mm.
Net weight kgs 2.5 kg.
Standard mounting Vertical wall.

CONFIRMING TO IP 65-DEGREE PROTECTION.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

cables & wireless co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI, NAGPUR -440023.

Tele Fax-07104-224381.

Cell: - 98226 95746 , 9822941190.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

“(Specifications and description subjected to change without prior notice)”