


# SMART CLEAN ROOM PHONE (MODEL CR-III-IP)

**SMART CLEAN ROOM PHONE** (MODEL CR-III-IP) is a vandal resistant, Polyester dial flush mount type CLEAN ROOM phone designed for use in clean rooms.

**CR-III-IP** offers hands-free communication over existing VOIP network for clean room environment. These telephone are connected via RJ45 to a 10/100 BaseT Ethernet.

These units come with one AUTO DIAL button and 4 X3 matrix standard keypad

The polyester front facia is resistant to most solvents. Concentrated minerals, concentrated caustic solution, high-pressure steam above 100°C, alcohol benzyn, and methylene chloride are a few solvents to be avoided.



## OPERATIONS:

### TO MAKE A CALL: -

- Press the on button, on hearing the dial tone dial the extn no of operator.
- When the call is answered, communicate using the mic & speaker.

### INCOMING CALL: -

- From any phone dial the extension number of SMART CLEAN ROOM PHONE.
- Electronic ringer will energise.
- Press on button to establish the call.
- Communicate using the mic & speaker.

## VERSATILE APPLICATIONS

\* Drugs and Pharma Units \* Biomedical Plants \* Pharmaceutical Plants \* Cement Plants. \* Mines. \* Petrochemical Refineries. \* Chemical Plants. \* Spinning Yarns \* Fertilizer Plants. \* Sugar Mills. \* Power Generation Facilities \* Pulp & Paper Mills \* Food Processing Plant \* Warehouses \* Recreation Facilities \* Hydroelectric Facilities \* Drilling Rigs \* Ammonia Storage Area \* Process industries \* ANY LARGE AND MEDIUM SCALE INDUSTRIAL UNITS.

## SMART CHOICE: -

- Operating on 220/110 V AC
- Simple Installation
- Simple Operation
- In built ringer & amplifier with volume control for internal speaker.
- 18 gauge rugged steel powder coated body
- Polyester front DIAL Plate.
- VOIP Design , SIP compatible
- Encapsulated circuit boards impervious to water and condensation.

## SPECIFICATIONS: -

### Electrical performance:-

Ringer sensitivity	40 - 100 V AC@ 16 - 25 Hz.
Ringer output	70 dB at 1 Mtr.
Speaker output	70 dB at 1 Mtr
Inbuilt Amplifier	3 Watts (RMS)

### NETWORK

Network Rate	10/100 Mbps
CONNECTOR	RJ-45 CAT-5 CONNECTOR PROVIDES ETHERNET COMMUNICATIONS
Protocol	Standard Internet Protocol (IP) is used for voice control and communications

### Environmental:-

Temperature	0 to +60 C.
Humidity	0 to 95% Rh non-condensing.
Enclosure	Dust proof.

### Mechanical

Body construction	18 SWG steel, powder coated body with FRONT AL DIAL plate.
Dimensions	230 x 230 x 60 mm.
Net weight	1.8 kgs.
Standard mounting	FLUSH/Wall mount.
Hardware material	Stainless steel.

**INDUSTRIAL COMMUNICATIONS SIMPLIFIED .**

# Voizlink.

FF 78 RAJAT ARCADE, MDC T-POINT,  
AMRAWATI ROAD, WADI,  
NAGPUR -440023, MAHARASHTRA, INDIA.  
PHONE: +917104-321913, +917104-224381  
FAX: +917104-224381.  
Cell: - +9198226 95746, +919822941190.  
Website: - [www.voizlink.in](http://www.voizlink.in).  
E-mail: - [info@voizlink.in](mailto:info@voizlink.in).

“(Specifications and description subjected to change without prior notice)”