

# SMART

# ELECTRONIC HOOTER CUM FLASHER

(MODEL-EH-FL)

**SMART ELECTRONIC HOOTER CUM FLASHER (MODEL-EH-FL)** is a solid-State Electronic Hooter of 30 Watt with a siren Tone of 40 sec with Sound output is 107 dB@ 1 meter

An Internal Volume control Pot is provided for output volume control, 2 external loud speaker horns of 8 ohms 60 Watt are connected with the unit.

The MAIN CONTROL CARD with power transformer is fitted in a wall mountable type IP 55/65 grade ABS body housing , weighing about 850gms with **military grade** connectors for speaker output & power input, Works on 220/110 V AC.

SMART LED FLASHER unit is RED COLOR NON MOTORISED LED flashing unit operating on 220 / 110 V AC supply and is connected to the HOOTER circuit for switching.

The FLASHER remains activates till HOOTER is active.

The positioning of the LOUD SPEAKERS determines the range of the system.

For all one direction sound both the speakers can be placed facing in one direction.

For two direction sound the speakers can be placed back to back.



## VERSATILE APPLICATIONS: -

- ❖ Cement Plants.
- ❖ Mines.
- ❖ Petrochemical Refineries
- ❖ Steel Plants.
- ❖ Spinning Yarns
- ❖ Fertilizer Plants.
- ❖ Sugar Mills
- ❖ Power Generation Facilities
- ❖ Pulp & Paper Mills
- ❖ Recreation Facilities
- ❖ Hydroelectric Facilities
- ❖ Drilling Rigs
- ❖ Process industries
- ❖ ANY LARGE AND MEDIUM SCALE INDUSTRIAL UNITS.

## SMART FEATURES: -

- ❖ Operating on 220/110 V AC (PREDEFINED)
- ❖ Siren Tone for 40 sec @ 30 Watt
- ❖ Sound output is 107 dB @ 1 meter.
- ❖ Internal Volume control Pot & 2 external loud speaker horns of 8 ohms 60
- ❖ ABS body with IP 55/65 grade
- ❖ Military grade connectors for speaker output & power input.
- ❖ Electronic Flasher visible from 100 meters range.

## **TECHNICAL SPECIFICATIONS: -**

### **ELECTRICAL: -**

Tone frequency range	300Hz to 1000Hz
Power Source	220/110 V AC (PREDEFINED)
Power consumption	< 35 Watt.
Stand by consumption	< 2 Watt.
Power output	30 Watt (RMS)
Sound output	107 dB @ 1 meter
Fuse	1 Amp 2AG fast blows.

### **ENVIRONMENTAL: -**

Temperature	0 to +60 C.
Humidity	0 to 95% Rh non-condensing.
Enclosure	Dustproof fully gasketed.

### **MECHANICAL: -**

Body	ABS.
SURFACE FINISH	MATT
Dimensions	200 x 160 x 29 mm.
Net weight Kgs	0.850 kg.
Standard mounting	Vertical/Horizontal wall.

**“(Specifications and description subjected to change without prior notice)”**

**INDUSTRIAL COMMUNICATION IS SIMPLIFIED**

**Voizlink.**

**FF 78 RAJAT ARCADE, MIDC T-POINT,  
AMRAWATI ROAD, WADI,  
NAGPUR –440023.MAHARASHTRA, INDIA.**

**PHONE: +917104-321913, +917104-224381**

**Fax: - +917104-224381.**

**Cell: - +9198226 95746, +919145427003, +919822941190.**

**Website: - [www.voizlink.in](http://www.voizlink.in)...E-mail: -[info@voizlink.in](mailto:info@voizlink.in).**